

### SPECIFICATION

#### TS-AG7203



**DESCRIPTION:** MEDIUM QUALITY MATERIAL CONTAINING FROM ASBESTOS FIBER JOINTING ONE SIDE COAT GRAPHITE.

**SERVICE:** SUITABLE FOR USE IN A WIDE RANGE OF APPLICATION, INCLUDING HOT WATER, SEAWATER STEAM, DILUTED, ACID & ALKALI, GASES, ALCOHOLS, SALT, SOLUTIONS AND ETC.

**STANDARD SIZE:** 1.3 M. x 1.5 M.

**THICKNESS:** 0.5, 1, 1.5, 2, 3 MM.

**COLOUR:** BLACK

<b>TENSILE STRENGTH</b>	Mpa	14.49
<b>RECOVERY</b>	%, ≥	43.5
<b>IGNITION LOSS</b>	%, ≤	21
<b>STRESS RELAXION</b>	%, ≥	50
<b>T MAX</b>	°C, ≤	350
<b>P MAX</b>	MPa ≤	3.8
<b>DENSITY</b>	g/cm <sup>3</sup>	1.9 ± 0.3
<b>COMPRESSIBILITY</b>	%	8.79 ~ 16.52
<b>AGING COEFFICIENT</b>	≥	0.92
<b>CREEP RELAXION</b>	%, ≤	50