



TrueSeal Pacific Co.,Ltd.

1561 SOI LADPRAW 94 SRIWARA RD., WANGTONGLANG, SUB DISTRICT,
WANGTONGLANG DISTRICT, BANGKOK 10310 THAILAND
TEL : 02-5590174-75, 02-5592425-27 FAX : 02-5592314

TS-3231/V PURE PTFE BRAIDED PACKING (DRY) SPECIFICATION

DESCRIPTION

BRAIDED FROM PURE PTFE YARN , PROVIDES A LOW FRICTION FINISH AND PREVENTS LEAKAGE THROUGH THE BRAID. IT IS MOST USEFUL IN SLOWER SHAFT SPEED APPLICATIONS. APPLICABLE FOR SEAL PACKING OF VALVES, VESSELS AND PUMPS OF CORROSIVE MEDIUM IN CHEMICAL, MEDICINE, FOOD.

RECOMMENDED USES

PACKING RECOMMENDED FOR PETROCHEMICAL INDUSTRY, FOOD INDUSTRY, BREWERIES
GENERALLY APPLICABLE

GENERAL PARAMETER

TECHNICAL DATA	ROTATING	RECIPROCATING	VALVES
PRESSURE	2 Mpa	15 Mpa	20 Mpa
SHAFT SPEED	10 M/S ROTARY		
TEMPERATURE	-200 °C to +260 °C		
PH RANGE	0 ~ 14		