



TrueSeal Pacific Co.,Ltd.

1561 SOI LADPRAW 94 SRIWARA RD., WANGTONGLANG, SUB DISTRICT
WANGTONGLANG DISTRICT, BANGKOK 10310 THAILAND
TEL : 02-5590174-75, 02-5592425-27 FAX : 02-5592314

TS-3233/GF

PTFE WITH GRAPHITE BRAIDED PACKING

SPECIFICATION

DESCRIPTION

BRAIDED FROM PTFE YARN WITH GRAPHITE, PROVIDES A LOW FRICTION FINISH AND PREVENTS LEAKAGE THROUGH THE BRAID. IT IS MOST USEFUL IN SLOWER SHAFT SPEED APPLICATIONS. APPLICABLE FOR SEAL PACKING OF VALVES, VESSELS AND PUMPS OF CORROSIVE MEDIUM IN CHEMICAL, MEDICINE

RECOMMENDED USES

PACKING RECOMMENDED FOR TANK HATCHES, MIXERS, CHEMICAL INDUSTRY AND PETROCHEMICAL INDUSTRY

GENERAL PARAMETER

TECHNICAL DATA	
PRESSURE	20 Mpa
SHAFT SPEED (M/S)	0-20 M/S ROTARY
TEMPERATURE	-200 °C to +280 °C
PH RANGE	0 ~ 14