



TrueSeal Pacific Co.,Ltd.

1561 SOI LADPRAW 94 SRIWARA RD., WANGTONGLANG, SUB DISTRICT,
WANGTONGLANG DISTRICT, BANGKOK 10310 THAILAND
TEL : 02-5590174-75, 02-5592425-27 FAX : 02-5592314



TS-4301/I

FLEXIBLE GRAPHITE BRAIDED PACKING WITH WIRE INSERT

SPECIFICATION

DESCRIPTION

BRAIDED PACKING OF EXPANDED, PURE GRAPHITE. THE PACKING BEHAVES AS AN EXPANDED GRAPHITE PRESSED RING WITH WIRE INSERT. THE CORROSION INHIBITOR ACTS AS A SACRIFICIAL ANODE TO PROTECT THE VALVE STEM AND STUFFING BOX.

RECOMMENDED USES

RECOMMEND CHOICE FOR HIGH TEMPERATURE FOR VALVE AND MANDOLD HAND HOLD OF STEAM BOILER

GENERAL PARAMETER

TECHNICAL DATA	RECIPROCATING	VALVES
PRESSURE	10 Mpa	30 Mpa
SHAFT SPEED	-	
TEMPERATURE	-200 °C to +455 °C ATMOSPHERE TO +650°C IN STEAM	
PH RANGE	0 ~ 14	