



TrueSeal Pacific Co.,Ltd.

1561 SOI LADPRAW 94 SRIWARA RD., WANGTONGLANG, SUB DISTRICT,
WANGTONGLANG DISTRICT, BANGKOK 10310 THAILAND
TEL : 02-5590174-75, 02-5592425-27 FAX : 02-5592314

TS-5292

SYNTHETIC FIBER IMPREGNATED WITH PTFE

SPECIFICATION

DESCRIPTION

MADE OF POLYACRYLONITRILE FILAMENT THROUGH REINFORCING, BRAIDING AND IMPREGNATED WITH PTFE, HAVING HIGH STRENGTH, WEAR-AND IMPACT AND APPLICABLE FOR PACKING SEAL OF PUMP, VALVE, AND VESSEL AT A HIGH LINE SPEED AND PRESSURE

RECOMMENDED USES

PACKING RECOMMENDED FOR PAPER INDUSTRY , REFINERIES, CHEMICAL INDUSTRY

GENERAL PARAMETER

TECHNICAL DATA	ROTATING	RECIPROCATING	VALVES
PRESSURE	2 Mpa	15 Mpa	20 Mpa
SHAFT SPEED	20 M/S ROTARY		
TEMPERATURE	-100 °C to +250 °C		
PH RANGE	2 ~ 12		