



TrueSeal Pacific Co.,Ltd.

1561 SOI LADPRAW 94 SRIWARA RD.,WANGTONGLANG, SUB DISTRICT,
WANGTONGLANG DISTRICT, BANGKOK 10310 THAILAND
TEL : 02-5590174-75, 02-5592425-27 FAX : 02-5592314

TS-5491

RAMIE IMPREGNATED WITH PTFE

SPECIFICATION

DESCRIPTION

DIAGONALLY BRAIDED PACKING MANUFACTURED FROM RAMIE YARNS, WHERE EACH STRAND IS IMPREGNATED IN A UNIQUE WAY WITH PTFE DISPERSION. THE PACKING IS THEN RE-IMPREGNATED WITH PTFE DISPERSION AND MINERAL LUBRICANTS FOR A GOOD RUNNING-IN PERIOD
RAMIE HAS HIGHER STRUCTURAL STRENGTH AND WILL TURN SOFT AFTER IN THE WATER.
THE PTFE EMULSION ENHANCES THE LUBRICANT ABILITY OF RAMIE

RECOMMENDED USES

PACKING RECOMMENDED FOR SHIPPING INDUSTRY, FOOD INDUSTRY, PAPER INDUSTRY AND BREWERIES



GENERAL PARAMETER

TECHNICAL DATA	ROTATING	RECIPROCATING	VALVES
PRESSURE	2 Mpa	2 Mpa	3 Mpa
SHAFT SPEED	8 M/S ROTARY		
TEMPERATURE	-50 °C to +260 °C		
PH RANGE	4 ~ 12		