



TrueSeal Pacific Co.,Ltd.

1561 SOI LADPRAW 94 SRIWARA RD., WANGTONGLANG, SUB DISTRICT,
WANGTONGLANG DISTRICT, BANGKOK 10310 THAILAND
TEL : 02-5590174-75, 02-5592425-27 FAX : 02-5592314



TS-7100

ASBESTOS IMPREGNATED WITH PTFE

SPECIFICATION

DESCRIPTION

BRAIDED PACKING OF ASBESTOS YARN WITH PTFE. HAVING HIGH WEAR AND SCOURING RESISTANCE AND COMPACTNESS , THEN IMPREGNATED WITH START-UP LUBRICANT FOR EASY ROTARY SERVICE.

RECOMMENDED USES

RECOMMEND CHOICE FOR TEMPERATURE ROTARY SLURRY SERVICE, ROTATING PUMP SEAL OF PUMPS, VALVES AND VESSELS , WATER TREATMENT.

GENERAL PARAMETER

TECHNICAL DATA	ROTATING	RECIPROCATING	VALVES
PRESSURE	5 Mpa	15Mpa	30 Mpa
SHAFT SPEED	11 M/S ROTARY		
TEMPERATURE	-50 °C to 260°C		
PH RANGE	0 ~ 12		